

# HERED®

## Telescopic Boom Lift HT20J

GB/CE/ANSI Compliance

### HIGHLIGHTS

- Quick action response and large operation radius.
- Fault self-diagnosis system.
- The industry's leading platform capacity with dual load capacity of 300kg / 450kg.
- Smooth telescopic boom control technology.
- Floating design, high passability and off-road capability.



### FEATURES

#### Standard

Automatic Leveling Platform

Horn

Self-diagnosis System

Proportional Control

Tilt Sensor

Motion Alarm

Swing Bridge

GPS

Flashing Beacons

Load Sensing System

Self-lock Gate

Color Display

Emergency Decent

Swing-out Engine Tray

Emergency Stop System

#### Optional

AC Power to the Platform



*Grand in Sound  
Sharp in Heart  
Viture in Action*

[sales@hrdlift.com](mailto:sales@hrdlift.com)

[www.hered-lift.com](http://www.hered-lift.com)

# HERED®

## Telescopic Boom Lift HT20J

GB/CE/ANSI Compliance

Models	HT20J
<b>Measurements</b>	
Max.Working Height	21.8m
Max.Platform Height	19.8m
Max.Horizontal Reach	16.6m
A-Length(Stowed)	9.76m
B-Width(Stowed)	2.49m
C-Height(Stowed)	2.77m
D-Platform Length	2.44m
E-Platform Width	0.91m
F-Wheel Base	2.5m
Wheel Track	2.1m
G-Ground Clearance	0.31m
<b>Performance</b>	
Max. Capacity(Unrestricted/Restricted)	300kg/450kg
Drive Speed(Stowed)	4.8km/h
Gradeability	45%
Turning Radius(In.)	2.42m
Turning Radius(Out.)	5.57m
Turntable Rotation	Continuous 360°
Platform Rotation	-80°—80°
Jib Rotation	-65°—78°
Max. Slope	5°
Max. Operating Wind Speed	12.5m/s
<b>Power</b>	
Power Source	Kubota V2403
Fuel Tank Capacity	130L
Control	12V
Hydraulic Tank Capacity	170L
Drive	AWD
Steering	Front Wheels
<b>Tires</b>	
Tires	355/55D 625—16
<b>Weight</b>	
Weight	12100kg

