

HERED®

Seld-Propelled Rough Terrain Scissor Lift

HS1623RT

GB/CE/ANSI Compliance

HIGH LIGHTS

- Strong off-road performance.
- Rough terrain tyre, large ground clearance, strong passing ability.
- Engine drives, more powerful.

FEATURES

Standard

Automatic Braking	Emergency Stop	Flashing Beacons
Proportional Control	Rolling-out Deck	Tilt Sensor
Emergency Descent	Folding Guardrails	Safety Arm
Hour Meter	Self-diagnosis	Self-lock gate
Motion Alarm	Horn	Charging Protection
		Outrigger

Optional

Working Lamp on the Platform
Load Sensing System
AC Power to the Platform
Air Pipe to the Platform
GPS



*Grand in Sound
Sharp in Heart
Viture in Action*

sales@hrdlift.com

www.hered-lift.com

HERED®

Seld-Propelled Rough Terrain Scissor Lift HS1623RT

GB/CE/ANSI Compliance

Models	HS1623RT
Measurements	
Max. Working Height	17.95m
A-Max. Platform Height	15.95m
Platform Dimension (B×C)	3.81×1.83m
Front Platform Extension Length	1.536m
Rear Platform Extension Length	1.231m
D-Overall Heights (Rails Up)	3.21m
Overall Height (Rails Folded)	2.44m
E-Overall Length (with Ladder)	4.88m
Overall Width with Outriggers	2.29m
G-Wheel Base	2862mm
H-Ground Clearanc	260mm
Performance	
Platform Capacity	680kg
Extension Capacity	230kg
Max. Occupancy	4Persons
Drive Height	8.5m
Drive Speed (Stowed)	6.1km/h
Drive Speed (Raised)	1.1km/h
Up/Down Time	55/65s
Turning Radius (Out.)	3.9m
Tilt Rating (Front to Rear/Side to Side)	3°/2°
Gradeability	40%
Max Outrigger Leveling (Front to Rear)	7°
Max Outrigger Leveling (Side to Side)	12°
Tires	
Tires Size (mm)	832×290mm
Power	
Hydraulic Oil Tank Capacity	120L
Fuel Tank Capacity	120L
Engine	KubotaV2403
Drive Type	4WD×2WS
Weight	
Weight	7980kg

