

# HERED®

## Slab Scissors

### E Series

GB/CE/ANSI Compliance

## HIGHLIGHTS

### More Efficient

- Doubled driving efficiency.
- Large platform capacity for severe working condition.
- FWD, Multi-disc braking, flexible maneuvering.

### Lower TCO

- Universal and modular design, easy maintenance.
- Swing out trays of batteries and hydraulic system.
- More durable, stable and safe.

## FEATURES

### Standard

Self-lock Gate	Folding Guardrails	Safety Arm
Pothole Guard	Emergency Stop	Tilt Sensor
Automatic Braking	Integrated Hour Meter	Charging Protection
Motion Alarm	Flashing Beacon	Forklift Pocket
Emergency Descent	Self-diagnosis	Horn
Full Height Drive	Rolling-out Deck	Proportional Control
GPS		

### Optional

Load Sensing System  
AC Power to the Platform  
Air Tube to the Platform



*Grand in Sound  
Sharp in Heart  
Viture in Action*

[sales@hrdlift.com](mailto:sales@hrdlift.com) [www.hered-lift.com](http://www.hered-lift.com)

# HERED®

## Self-Propelled Scissors

### E Series

GB/CE/ANSI Compliance

Models	HS0407E	HS0507WE	HS0607E	HS0608E	HS0808E	HS0812E	HS1012E	HS1212E	HS1413E
<b>Measurements</b>									
<b>Max. Working Height</b>	5.6m	6.3m	7.8m	7.9m	9.9m	9.8m	11.8m	13.8m	15.7m
<b>A-Max. Platform Height</b>	3.6m	4.3m	5.8m	5.9m	7.9m	7.8m	9.8m	11.8m	13.7m
<b>B-Platform Length</b>	1.35m	1.35m	1.63m	2.26m	2.26m	2.26m	2.62m	2.62m	2.64m
<b>C-Platform Width</b>	0.7m	0.7m	0.74m	0.81m	0.81m	1.12m	1.12m	1.12m	1.14m
<b>Extension Size</b>	0.6m	0.6m	0.9m	0.9m	0.9m	0.9m	0.9m	0.9m	0.9m
<b>D-Height(Rails Up)</b>	2.05m	2.15m	2.1m	2.15m	2.27m	2.28m	2.4m	2.56m	2.71m
<b>Height(Rails Down)</b>	1.65m	1.89m	1.83m	1.84m	1.96m	1.68m	1.8m	1.96m	2.2m
<b>E-Length(with Ladder)</b>	1.53m	1.53m	1.86m	2.47m	2.47m	2.49m	2.49m	2.49m	2.86m
<b>F-Overall Width</b>	0.76m	0.81m	0.76m	0.81m	0.81m	1.18m	1.18m	1.19m	1.25m
<b>G-Wheel Base</b>	1.12m	1.12m	1.32m	1.85m	1.85m	1.85m	1.85m	1.85m	2.24m
<b>H-Clearance(Stowed)</b>	0.05m	0.05m	0.06m	0.1m	0.1m	0.1m	0.1m	0.1m	0.1m
<b>I-Clearance(Raised)</b>	0.02m	0.02m	0.02m	0.02m	0.02m	0.02m	0.02m	0.02m	0.02m
<b>Performance</b>									
<b>Platform Capacity</b>	240kg	230kg	230kg	380kg	230kg	450kg	320kg	320kg	250kg
<b>Extension Capacity</b>	113kg	113kg	113kg	113kg	113kg	113kg	113kg	113kg	113kg
<b>Max. Occupancy</b>	2	2	2	2	2	2	2	2	2
<b>Drive Speed(Stowed)</b>	4km/h	4km/h	4km/h	3.5km/h	3.5km/h	3.5km/h	3.5km/h	3.5km/h	3.5km/h
<b>Drive Speed(Raised)</b>	0.5km/h	0.5km/h	0.8km/h	0.8km/h	0.8km/h	0.8km/h	0.8km/h	0.8km/h	0.8km/h
<b>Turning Radius(In.)</b>	0.3m	0.3m	0m	0m	0m	0m	0m	0m	0m
<b>Turning Radius(Out.)</b>	1.5m	1.5m	1.55m	2.1m	2.1m	2.3m	2.3m	2.3m	2.3m
<b>Up/Down Time</b>	25/25s	25/20s	16/34s	30/34s	31/40s	35/40s	62/39s	65/60s	80/60s
<b>Gradeability</b>	25%	25%	25%	30%	25%	25%	25%	25%	25%
<b>Max. Slope</b>	1.5°/3°	1.5°/3°	1.5°/3°	1.5°/3°	1.5°/3°	1.5°/3°	2°/3°	1.5°/3°	1.5°/3°
<b>Control</b>	Switching			Proportional					
<b>Drive</b>	RWD	RWD	FWD	FWD	FWD	FWD	FWD	FWD	FWD
<b>Multi Disc Brake</b>	Rear	Rear	Front	Front	Front	Front	Front	Front	Front
<b>Tires(mm)</b>	230×80	230×100	305×102	381×127	381×127	381×127	381×127	381×127	381×127
<b>Power</b>									
<b>Batteries(V/Ah)</b>	2x12/85	2x12/85	4X6/210	4X6/225	4X6/225	4X6/240	4X6/240	4X12/300	4X12/300
<b>Charger</b>	100-240V/AC/15A	100-240V/AC/15A	100-240V/AC/30A	100-240V/AC/30A	100-240V/AC/30A	100-240V/AC/30A	100-240V/AC/30A	100-240V/AC/30A	100-240V/AC/30A
<b>Weight</b>									
<b>Weight</b>	880kg	990kg	1430kg	2050kg	2180kg	2655kg	2810kg	2980kg	3330kg

